



HeliPrimer WB

Water based primer for porous surfaces

HeliPrimer WB is a water based primer used when coatings are applied to porous substrates. HeliPrimer WB is also used both as a pre-sealer and as a curing aid for concrete repair mortar.

Description

HeliPrimer is an aqueous dispersion of an acrylic copolymer containing coalescents and a biocide.

Directions for Use

1. Substrate Preparation

The substrate to be primed must be sound, clean and free from oils, release agents, residues of paint, micro organic growth and dust. Cracks should be repaired, "blowholes" should be filled and any joint sealants masked prior to the application of the primer.

2. Application

HeliPrimer WB is supplied ready for application although containers should be shaken immediately prior to use. The primer can be applied by brush, roller or, on large uninterrupted areas, by spray. Any coating should be applied when the WB Primer is touch-dry.

Typical coverage rate: 10m² per litre.

Coverage is dependent upon surface texture, porosity and application technique. The above figure is quoted as a guide.

3. Cleaning

Tools should be cleaned immediately after use with clean water.

Performance Data

| | |
|-------------------|------------|
| Density | 1.02kg/l |
| Particle size | 0.2 micron |
| Percentage solids | 23% |

Storage

HeliPrimer WB should be stored under dry, frost-free conditions in air tight plastic containers. The shelf life under such conditions will be at least 12 months. Primer which has been exposed to frost should **not** be used. All packs should be shaken well before use.

Packaging

HeliPrimer WB is supplied in 5 litre units.

Health and Safety

HeliPrimer WB is not currently classified as a hazardous material. However, normal precautions for the handling of chemicals must be observed.

Gloves, eye protection and suitable overalls should be worn. Personal hygiene should be observed. Hands should be washed after use.

Prolonged contact with the skin may cause irritation in certain individuals.

Safety data sheets are available.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company. It is the customer's responsibility to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable and that in the light of our continual research and development programme the information relating to each product has not been superseded.

Information and Sales:



Unit 24, 34-36 Ralph Street, Alexandria NSW 2015

Tel: 1300 66 7071 Fax: (02) 9669 1702

e-mail: sales@helifix.com.au web site: www.helifix.com.au